

LATERAL VOID FILLERS

Cargo Protect+ delivers better freight protection at a lower total cost.

01 / Details

Prevent Load Shifting

Palletized goods can lean and fall into the empty spaces of a load often resulting in additional unload time and damaged products. Fill the space by easily sliding Lateral Void Fillers into place.

- Use between pallets or product and interior walls of a truck, sea container, or rail car
- Use instead of drop down filler



**REDUCES DAMAGES
BY UP TO 80%**


**INCREASES PRODUCT
QUANTITY PER SHIPMENT**



Slides easy into place



Easy to assemble



Nestable design

02 / Specifications

1618 Lateral Void Filler

- Withstands 2,500 lbs of force
- 96"h x 40"w x 9"d - 29 lbs
- Snap two together for 18" spacing - reversed for 16" spacing
- Can fit 1,125 in return shipments
- Fail-safe design to fill void
- Parts are nestable for return shipments

814 Lateral Void Filler

- Withstands 2,500 lbs of force
- 120"h x 40"w x 7"d - 30.8 lbs
- Snap two together for 14" spacing - reversed for 8" spacing
- Can fit 800 in return shipments
- Fail-safe design to fill void
- Parts are nestable for return shipments

1420 Lateral Void Filler

- Withstands 2,500 lbs of force
- 62"h x 36"w x 10"h - 15 lbs
- Snap two together for 20" spacing - reversed for 14" spacing
- Can fit 2,025 in return shipments
- Fail-safe design to fill void
- Parts are nestable for return shipments

LATERAL VOID FILLERS

FEATURES



- Energy absorbing- cushions without crushing
- Lightweight rigid parts enable fast loading
- Ergonomic hand holes ensure easy handling
- Splinter-free & lightweight HDPE material reduces dock related injuries
- Weather & moisture resistance allows outside storage to optimize warehouse space
- Easy to clean surfaces are beneficial for use with a variety of commodities



CARGO PROTECT+ ADVANTAGES

- Environmentally Friendly
- ISPM 15 Exempt
- Long Service Life



Easy
Clean



Sanitary



Weather
Resistant



Impact
Resistant



Recycle

TriEnda publishes standard guidelines for its products, based on its testing standards, and, as such, these guidelines do not constitute any warranty related to each customer's individual application. The material handling industry has not standardized on test methodology and rating criteria for each individual product. All TriEnda products are sold with the understanding that the customer will validate for themselves the suitability of the product for their specific application. As each product application is unique, the customer assumes all risks associated with the determination and actual use of the pallet.



CONTACT US

N7660 Industrial Road Portage, WI 53901
www.triend.com | sales@triend.com
1-800-356-8150

**PALLET
BUYBACK
PROGRAM**

